

# Bis






















Lampade da parete-soffitto con diffusore in vetro opale satinato soffiato a bocca, e struttura in policarbonato anti UV traslucido neutro resistente al cloro (Bis) o con strutture in metallo verniciato bianco (Bis Bayonet). Entrambi i modelli hanno la chiusura del vetro a baionetta. Il prodotto è adatto esclusivamente all'uso interno. Il modello Bis ha un grado di protezione IP44 lo rende particolarmente indicato per piscine e ambienti umidi in genere.











Wall-ceiling lamps with diffuser in mouth blown, satin-finish opal glass; frame in chlorine-resistant, anti-UV, neutral translucent polycarbonate (Bis) or in white painted metal (Bis Bayonet). Both models have a twist-lock coupling system for the glass component. The product is suitable for internal use only; although the model Bis has an IP44 rating that makes it ideal for use in swimming pools and humid environments in general.
















Bis Bayonet wall-ceiling lamp → **LD611203**

| SPECIFICHE<br>SPECIFICATIONS   | DATI TECNICI<br>TECHNICAL DATA   | FINITURE<br>FINISHES  | CODICE<br>CODE                                     |                   |
|--|--|---|--|-------------------|
| parete-soffitto<br>wall-ceiling<br><br><br>Ø 31 x 10 cm<br>Ø 12,2 x 3,9 in | <b>E27</b><br>220-240V   1x42W<br><b>IP44</b>  |  Trasparente / Clear | <b>LL6111NE</b>                                    |                   |
|  | <b>LED</b><br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP44</b>   |  Trasparente / Clear | <b>LED 2700-4000K</b><br>su richiesta / on request | <b>LD6111NE</b>   |
|  | <b>LED TRIAC</b> <br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP44</b> |  Trasparente / Clear |  | <b>LD61113NE</b>  |
|  | <b>LED DALI</b> <br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP44</b>  |  Trasparente / Clear |  | <b>LD611123NE</b> |
|  | <b>LED WI-FI</b> <br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP44</b> |  Trasparente / Clear |  | <b>LD611133NE</b> |

|   |   |   |  |                   |
|---|---|---|--|-------------------|
| parete-soffitto<br>wall-ceiling<br><br><br>Ø 40 x 13 cm<br>Ø 15,7 x 5,1 in                                | <b>E27</b><br>220-240V   2x42W<br><b>IP44</b>   |  Trasparente / Clear   | <b>LL6112NE</b>                                    |                   |
|   | <b>LED</b><br>220-240V   3000K   CRI>90  <br>19,5W   2100lm   beam angle 122°<br><b>IP44</b>  |  Trasparente / Clear   | <b>LED 2700-4000K</b><br>su richiesta / on request | <b>LD6112NE</b>   |
|   | <b>LED EMERGENCY (3h)</b><br>220-240V   3000K   CRI>90  <br>5-18,5W   2100lm   beam angle<br>122°<br><b>IP44</b>  |  Trasparente / Clear |  | <b>LD612603NE</b> |
|   | <b>LED TRIAC</b> <br>220-240V   3000K   CRI>90  <br>18,5W   2100lm   beam angle<br>122°<br><b>IP44</b> |  Trasparente / Clear |  | <b>LD611213NE</b> |
|   | <b>LED DALI</b> <br>220-240V   3000K   CRI>90  <br>18,5W   2100lm   beam angle<br>122°<br><b>IP44</b>  |  Trasparente / Clear |  | <b>LD611223NE</b> |
| <b>LED WI-FI</b> <br>220-240V   3000K   CRI>90  <br>18,5W   2100lm   beam angle<br>122°<br><b>IP44</b> |  Trasparente / Clear   |   | <b>LD611233NE</b>                                  |                   |

| SPECIFICHE<br>SPECIFICATIONS   | DATI TECNICI<br>TECHNICAL DATA   | FINITURE<br>FINISHES  | CODICE<br>CODE                                     |                   |
|--|--|---|--|-------------------|
| parete-soffitto<br>wall-ceiling<br><br><br>Ø 48 x 13 cm<br>Ø 18,9 x 5,1 in                        | <b>E27</b><br>220-240V   3x42W<br><b>IP44</b>  |  Trasparente / Clear | <b>LL6113NE</b>                                    |                   |
|  | <b>LED</b><br>220-240V   3000K   CRI>90   30W<br>  3000lm   beam angle 116°<br><b>IP44</b>   |  Trasparente / Clear | <b>LED 2700-4000K</b><br>su richiesta / on request | <b>LD6113NE</b>   |
|  | <b>LED EMERGENCY (3h)</b><br>220-240V   3000K   CRI>90  <br>5-29W   3000lm   beam angle<br>166°<br><b>IP44</b>   |  Trasparente / Clear |  | <b>LD612703NE</b> |
|  | <b>LED TRIAC</b> <br>220-240V   3000K   CRI>90   29W<br>  3000lm   beam angle 116°<br><b>IP44</b> |  Trasparente / Clear |  | <b>LD611313NE</b> |
|  | <b>LED DALI</b> <br>220-240V   3000K   CRI>90   29W<br>  3000lm   beam angle 116°<br><b>IP44</b>  |  Trasparente / Clear |  | <b>LD611323NE</b> |
| <b>LED WI-FI</b> <br>220-240V   3000K   CRI>90   29W<br>  3000lm   beam angle 130°<br><b>IP44</b> |  Trasparente / Clear  |   | <b>LD611333NE</b>                                  |                   |

| SPECIFICHE<br>SPECIFICATIONS  | DATI TECNICI<br>TECHNICAL DATA  | FINITURE<br>FINISHES | CODICE<br>CODE  |
|---|---|----------------------|---|
| parete-soffitto<br>wall-ceiling<br>   | <b>E27</b><br>220-240V   1x42W<br><b>IP20</b>   | Bianco / White       | <b>LL6110</b>   |
| Ø 25 x 9 cm<br>Ø 9,8 x 3,5 in   | <b>LED</b><br>220-240V   3000K   CRI>80   10W<br>  1463lm   beam angle 130°<br><b>IP20</b>  | Bianco / White       | <b>LED 2700-4000K</b><br>su richiesta / on request<br><b>LD611003</b> |
| parete-soffitto<br>wall-ceiling<br>   | <b>E27</b><br>220-240V   1x52W<br><b>IP20</b>   | Bianco / White       | <b>LL6111</b>   |
| Ø 31 x 10 cm<br>Ø 12,2 x 3,9 in   | <b>LED</b><br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP20</b>  | Bianco / White       | <b>LED 2700-4000K</b><br>su richiesta / on request<br><b>LD611103</b> |
|   | <b>LED TRIAC</b> <br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP20</b>      | Bianco / White       | <b>LD611113</b>   |
|   | <b>LED DALI</b> <br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP20</b>       | Bianco / White       | <b>LD611123</b>   |
|   | <b>LED WI-FI</b> <br>220-240V   3000K   CRI>90  <br>12,5W   1350lm   beam angle 127°<br><b>IP20</b>      | Bianco / White       | <b>LD611133</b>   |
| parete-soffitto<br>wall-ceiling<br> | <b>E27</b><br>220-240V   2x52W<br><b>IP20</b>   | Bianco / White       | <b>LL6112</b>   |
| Ø 40 x 13 cm<br>Ø 15,7 x 5,1 in   | <b>LED</b><br>220-240V   3000K   CRI>90  <br>19,5W   2100lm   beam angle 122°<br><b>IP20</b>  | Bianco / White       | <b>LED 2700-4000K</b><br>su richiesta / on request<br><b>LD611203</b> |
|   | <b>LED EMERGENCY (3h)</b><br>220-240V   3000K   CRI>90  <br>5-18,5W   2100lm   beam angle<br>122°<br><b>IP20</b>  | Bianco / White       | <b>LD612603</b>   |
|   | <b>LED TRIAC</b> <br>220-240V   3000K   CRI>90  <br>18,5W   2100lm   beam angle<br>122°<br><b>IP20</b> | Bianco / White       | <b>LD611213</b>   |
|   | <b>LED DALI</b> <br>220-240V   3000K   CRI>90  <br>18,5W   2100lm   beam angle<br>122°<br><b>IP20</b>  | Bianco / White       | <b>LD611223</b>   |
|   | <b>LED WI-FI</b> <br>220-240V   3000K   CRI>90  <br>18,5W   2100lm   beam angle<br>122°<br><b>IP20</b> | Bianco / White       | <b>LD611233</b>   |

| SPECIFICHE<br>SPECIFICATIONS   | DATI TECNICI<br>TECHNICAL DATA   | FINITURE<br>FINISHES | CODICE<br>CODE  |
|--|--|----------------------|---|
| parete-soffitto<br>wall-ceiling<br> | <b>E27</b><br>220-240V   3x52W<br><b>IP20</b>  | Bianco / White       | <b>LL6113</b>   |
| Ø 48 x 13 cm<br>Ø 18,9 x 5,1 in  | <b>LED</b><br>220-240V   3000K   CRI>90   30W<br>  3000lm   beam angle 116°<br><b>IP20</b>   | Bianco / White       | <b>LED 2700-4000K</b><br>su richiesta / on request<br><b>LD611303</b> |
|  | <b>LED EMERGENCY (3h)</b><br>220-240V   3000K   CRI>90  <br>5-29W   3000lm   beam angle<br>116°<br><b>IP20</b>   | Bianco / White       | <b>LD612703</b>   |
|  | <b>LED TRIAC</b> <br>220-240V   3000K   CRI>90   29W<br>  3000lm   beam angle 116°<br><b>IP20</b> | Bianco / White       | <b>LD611313</b>   |
|  | <b>LED DALI</b> <br>220-240V   3000K   CRI>90   29W<br>  3000lm   beam angle 116°<br><b>IP20</b>  | Bianco / White       | <b>LD611323</b>   |
|  | <b>LED WI-FI</b> <br>220-240V   3000K   CRI>90   29W<br>  3000lm   beam angle 116°<br><b>IP20</b> | Bianco / White       | <b>LD611333</b>   |