# Pencil \_Lighting module



Pencil is a battery-operated portable and rechargeable lighting module, available in three sizes. A "touch" control on one end allows switching on/off, dimming (4-step: 100%, 60%, 30%, 6%) and selecting the color temperature of the light (2700 K, 3150 K or 4000 K). It is suitable for both indoor and outdoor use and salt spray resistant (1500 h). An electronic control system monitors the remaining autonomy and ensures a constant luminous flux until the battery runs out. Recharging is therefore optimized and always properly done. The lighting module can be recharged in two ways: either with the battery charger (pg. 182) or in the docking station, connected to a battery charger (pg. 184). The battery charger is not included.



# Pencil \_Lighting module

# **Lighting specifications**

source LED
type SMD
total power 18.0 W
power LED 15.0 W
color temperature 2700 - 3150

 color temperature
 2700 - 3150 - 4000 K

 lumen lamp
 1340 - 1500 - 1700 lm

 lumen LED
 1740 - 1950 - 2040 lm

beam angle 100°
CRI > 90
class E

dimmer TOUCH DIMMER

motion sensor NO

# **Electrical specifications**

classe 3

supply voltage 19Vdc max.2.5A

battery 9 cell li-ion battery pack mod. 26650

11,1v - 15000 ma/h


battery life 100% 8 h. - 60% 13 h. - 30% 28 h. -

6% 58 h.

charging time 12 H.

### **ACCESSORIES**

## LD0800CS



5 cm •12 cm •4 cm •18.0 W •IP20 •100-240V• 50/60 Hz





LD0810



Ø 20 cm •32 cm •IP20 • • 50/60 Hz








Black





# LD0812




4.7 cm •3.7 cm •500 cm • • 50/60 Hz




White	ВЗ
Dark gray	G3



### LD0813



### LD081400



9 cm •12 cm •28 cm •• 50/60 Hz



# Pencil \_Lighting module

# 4.7 cm •3.8 cm •6.4 cm • •50/60 Hz CE III White B3 R3