

Poldina micro _Table



Poldina micro is a rechargeable battery-powered cordless table lamp. A "touch" control on the head allows switching on/off, dimming, and selecting the color temperature of the light (2200 K, 2700 K or 3000 K). It is suitable for both indoor and outdoor use (except gold and silver finishes). An electronic control system monitors the remaining autonomy and ensures a constant luminous flux until the battery runs out. Recharging is therefore optimized and always properly done. The lamp comes with a contact charging base; the battery charger is not included.

Ø 7 cm
Ø 2,8 in



27,5 cm
10,8 in

7 x 7 cm
2,8 x 2,8 in



5,8 cm
2,3 in

0,8 cm
0,3 in

LED sostituibile da utente

dimmable

IP65

LD0490

	White	B3		Black	D3
	Dark gray	N3		Sage green	G3
	Sand	S3		Red	F3
	Pink	P3		Lilac	L3
	Capri blue	K3		Orange	Z3
	Apple green	V3		Chrome	C3
	Glossy gold	O3			
	Not suitable for outdoor use				
	Black - Gold color leaf	DFO		Red - Gold color leaf craquelé	FFO
	Not suitable for outdoor use			Not suitable for outdoor use	
	Capri blue - Gold color leaf craquelé	KFO			



DESIGN IN ITALY BY ZAFFERANO SRL, China

Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso - Italy www.zafferanoitalia.com

The company reserves the right to modify product specifications.

For more information visit www.zafferanoitalia.com

zafferano
LAMPES-À-PORTER

Poldina micro _Table

Lighting specifications

source	LED sostituibile da utente
type	SMD
total power	18 W
power LED	16 W
color temperature	2200 - 2700 - 3000 K
lumen lamp	124 - 128 - 142 lm
lumen LED	174 - 177 - 195 lm
beam angle	50°
CRI	> 80
class	F
dimmer	TOUCH DIMMER
motion sensor	NO

Electrical specifications

classe	3
input	100-240V
output	5 Vdc max 1A
battery	1 cell li-ion battery pack mod. 104040 3,7v - 1900 ma/h
battery life	7/8 H.
charging time	3 H.

ACCESSORIES

LD0340RA




6 cm • 135 cm • 45 cm • 18 W
• IP20 • 100-240V • 50/60 Hz



Black

LD0490RP




33 cm • 51 cm • 58 cm • 18 W
• IP20 • 100-240V • 50/60 Hz



Black

LD0490UA




25 cm • 4 cm • 8 cm • IP20
• 100-240V • 50/60 Hz



White

LD0490RB



67 cm • 67 cm • 9 cm • IP20
• 5Vdc max.1A • 50/60 Hz

Black