


## Pencil \_Lighting module



Pencil is a battery-operated portable and rechargeable lighting module, available in three sizes. A "touch" control on one end allows switching on/off, dimming (4-step: 100%, 60%, 30%, 6%) and selecting the color temperature of the light (2700 K, 3150 K or 4000 K). It is suitable for both indoor and outdoor use and salt spray resistant (1500 h). An electronic control system monitors the remaining autonomy and ensures a constant luminous flux until the battery runs out. Recharging is therefore optimized and always properly done. The lighting module can be recharged in two ways: either with the battery charger (pg. 182) or in the docking station, connected to a battery charger (pg. 184). The battery charger is not included.

5,4 cm  
2,1 in





146 cm  
57,4 in

LED sostituibile da tecnico

dimmable

IP65

### LD0802

	White	B3		R3
		G3		



DESIGN IN ITALY BY ZAFFERANO SRL, China

Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso  
- Italy [www.zafferanoitalia.com](http://www.zafferanoitalia.com)

# Pencil \_Lighting module

## Lighting specifications


source	LED sostituibile da tecnico
type	SMD
total power	180 W
power LED	150 W
color temperature	2700 - 3150 - 4000 K
lumen lamp	1340 - 1500 - 1700 lm
lumen LED	1740 - 1950 - 2040 lm
beam angle	100°
CRI	> 90
class	E
dimmer	TOUCH DIMMER
motion sensor	NO

## Electrical specifications

classe	3
input	100-240V
output	19 Vdc max 25 A
battery	9 cell li-ion battery pack mod. 26650 11,1v - 15000 ma/h
battery life	100% 8 h. - 60% 13 h. - 30% 28 h. - 6% 58 h.
charging time	12 H.

## ACCESSORIES

### LD0800CS



5 cm • 12 cm • 4 cm • 180 W  
• IP20 • 100-240V • 50/60 Hz



■ Black

### LD0810



∅ 20 cm • 32 cm • IP20 •  
• 50/60 Hz



■ White B3  
■ G3

■ R3

### LD0811




47 cm • 37 cm • 3 cm • 500 cm •  
• 50/60 Hz



■ White B3  
■ G3

■ R3

### LD0812



47 cm • 37 cm • 500 cm •  
• 50/60 Hz



■ White B3  
■ G3

■ R3

### LD0813




25 cm • 3 cm • 100 cm •  
• 50/60 Hz



■ White B3  
■ G3

■ R3

### LD081400



9 cm • 12 cm • 28 cm • 50/60 Hz



■ Clear



# Pencil \_Lighting module

LD0815




47 cm • 38 cm • 64 cm •  
• 50/60 Hz



	White	B3
		R3


G3

LD0816



Ø 20 cm • 22 cm • IP20 •  
• 50/60 Hz



	White	B3
		G3

		R3
-------------------------------------------------------------------------------------	--	----