

# Mariposa \_wall-ceiling

Wall-ceiling lamps with diffuser in handcrafted plate glass, available in two shapes: square and round.

The diffuser is available in various colors: transparent, amber, amethyst, and grey for the square lamp; with the addition of light blue for the round lamp.

The frame is made of white painted metal with chrome details.

These new versions have been redesigned with a dimmable LED light source, which not only increases the wattage and luminous efficiency but also ensures they comply with the minimum requirements of the Ecodesign Regulation.

Each product is provided with accessory lenses to increase the aperture of the light beam.

Mariposa is designed for modular use and can be customized in colors and finishes. Suitable for indoor use only.

Wall-ceiling lamps.

The diffuser is available in various colors: transparent, amber, amethyst, and grey for the square lamp; with the addition of light blue for the round lamp.


The frame is made of white painted metal with chrome details.

These new versions have been redesigned with a dimmable LED light source, which not only increases the wattage and luminous efficiency but also ensures they comply with the minimum requirements of the Ecodesign Regulation.


Each product is provided with accessory lenses to increase the aperture of the light beam.

Mariposa is designed for modular use and can be customized in colors and finishes. Suitable for indoor use only.

26 cm  
10,2 in




16 cm  
6,3 in



LED IP20

**LMR0300**

Matte white



11,5 cm  
4,5 in



**DESIGN IN ITALY BY ZAFFERANO SRL, MADE IN PRC**

Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso - Italy [www.zafferanoitalia.com](http://www.zafferanoitalia.com)

# Mariposa \_wall-ceiling

## Lighting specifications

---

source	LED
type	COB
total power	2x6.0 W
power LED	2x6.0 W
color temperature	3000 K
lumen lamp	2x490 lm
lumen LED	2x490 lm
beam angle	145°
CRI	> 90
source class	G
dimmer	TRIAC
motion sensor	NO

## Electrical specifications

---

class	1
voltage	220-240V
frequency	50/60 Hz

## ACCESSORIES

---