


Bis _wall-ceiling



Wall-ceiling lamps with diffuser in mouth-blown, satin-finish opal triplex glass; chlorine-resistant, anti-UV, neutral translucent polycarbonate frame. Twist-lock system for the glass component. The product is suitable for indoor use only. The IP44 rating makes it ideal for use in swimming pools and humid environments in general.



13 cm
5,1 in



Ø48 cm
Ø18,9 in

LED sostituibile da utente

dimmable

IP44

LD611323

NE



DESIGN IN ITALY BY ZAFFERANO SRL, China

Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso
- Italy www.zafferanoitalia.com

Bis _wall-ceiling

Lighting specifications

| | |
|-------------------|----------------------------|
| source | LED sostituibile da utente |
| type | SMD |
| total power | 29 W |
| power LED | 24 W |
| color temperature | 3000 K |
| lumen lamp | 2070 lm |
| lumen LED | 3000 lm |
| beam angle | 116° |
| CRI | > 90 |
| class | E |
| dimmer | DALI |
| motion sensor | NO |

Electrical specifications

| | |
|-----------|----------|
| classe | 1 |
| voltage | 220-240V |
| frequency | 50/60 Hz |
| input | 220-240V |
| output | 12 A |

ACCESSORIES
