


Poldina mini _Table




Poldina mini is a rechargeable battery-powered cordless table lamp. A "touch" control on the head allows switching on/off, dimming, and selecting the color temperature of the light (2200 K, 2700 K or 3000 K). It is suitable for both indoor and outdoor use (except gold, silver, and copper finishes). An electronic control system monitors the remaining autonomy and ensures a constant luminous flux until the battery runs out. Recharging is therefore optimized and always properly done. Poldina comes with a contact charging base; the battery charger is included. The lamp can be customized with a ceramic cover, to be purchased separately

Ø 11 cm
Ø 4,3 in














10 x 10 cm
3,9 x 3,9 in



LED dimmable IP65

LD0320

	White	B3		Corten	R3
	Dark gray	N3		Sand	S3
	Gold color leaf	BFO		Silver color leaf	BFA
Not suitable for outdoor use			Not suitable for outdoor use		
	Copper color leaf	RFR		Glossy gold	O3
Not suitable for outdoor use			Not suitable for outdoor use		
	Glossy chrome	C3			
Not suitable for outdoor use					



DESIGN IN ITALY BY ZAFFERANO SRL,MADE IN PRC
Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso
- Italy www.zafferanoitalia.com

Poldina mini _Table


Lighting specifications		Electrical specifications	
source	LED	supply voltage	5Vdc max.1A
type	SMD	frequency	50/60 Hz
total power	2,2 W	input	100-240V
power LED	2,0 W	output	5 Vdc max 1A
color temperature	2200 - 2700 - 3000 K	battery	2 cell li-ion battery pack mod. 18650 3,7v - 2200 ma/h
lumen lamp	185 - 199 - 203 lm	battery life	12 H.
lumen LED	234 - 251 - 256 lm	charging time	6/7 H.
beam angle	45°		
CRI	> 80		
class	F		
dimmer	TOUCH DIMMER		
motion sensor	NO		

ACCESSORIES

LD0340RA




6 cm •13.5 cm •4.5 cm •2,2 W
•IP20 • 100-240V• 50/60 Hz




Black

LD0350RB




9.4 cm •9.4 cm •IP20 • 100-240V
• 50/60 Hz




Black

LD0350RP



33 cm •51 cm •5.8 cm •2,2 W
•IP20 • 100-240V• 50/60 Hz



Black

LD0350



Ø 13 cm •10 cm •• 50/60 Hz

Green stripes	00
Blue stripes	02
Light blue fish	04

Yellow stripes	01
Red stripes	03
	10