


Bis _wall-ceiling



Wall-ceiling lamps with diffuser in mouth-blown, satin-finish opal triplex glass; chlorine-resistant, anti-UV, neutral translucent polycarbonate frame. Twist-lock system for the glass component. The product is suitable for indoor use only. The IP44 rating makes it ideal for use in swimming pools and humid environments in general.



10 cm
3,9 in



Ø31 cm
Ø12,2 in

LED sostituibile da utente

dimmable

IP44

LD611123

NE



DESIGN IN ITALY BY ZAFFERANO SRL, China

Zafferano SRL - Viale dell'Industria, 26 31055 Quinto di Treviso
- Italy www.zafferanoitalia.com

Bis _wall-ceiling

Lighting specifications

| | |
|-------------------|----------------------------|
| source | LED sostituibile da utente |
| type | SMD |
| total power | 125 W |
| power LED | 105 W |
| color temperature | 3000 K |
| lumen lamp | 1110 lm |
| lumen LED | 1350 lm |
| beam angle | 127° |
| CRI | > 90 |
| class | E |
| dimmer | DALI |
| motion sensor | NO |

Electrical specifications

| | |
|-----------|----------|
| classe | 1 |
| voltage | 220-240V |
| frequency | 50/60 Hz |
| input | 220-240V |
| output | 450 mA |

ACCESSORIES
